

Replace your CO alarms that are over 5 years old!

TM

Mini Carbon Monoxide Alarm

• Microprocessor technology programmed to detect Carbon Monoxide levels using Time Weighted Average (TWA) at 10% COHb curves.

- No False Alarms from new boat smell or outgassing.
- Full 5 year service life. End of Life clock starts when power is applied, not in inventory or on retail shelves.
- No nuisance alarms caused by temporary background levels of CO.
- Memory Scan. Retains the CO level that activated the alarm. After ventilation, it is impossible to know what the CO level was unless your detector has memory.
- Alarm Mute button silences alarm while boat is ventilated.
- Low Current Draw. Innovative micro current circuit saves precious battery power. 37 milliamp (.037 amp.) current draw.
- 62-541-R-Marine and 62-542-R-Marine include normally closed relay. Use to turn on exhaust fans, remote horns/lights/signals or connect to alarm systems.
- NMMA Listed Component.

- Meets ABYC A-24 Standard CARBON MONOXIDE DETECTION SYSTEMS.
- Listed to UL 2034 Carbon Monoxide Alarms Marine Use and CSA 6.19-01.
- Meets ISO: 12133 Small craft Carbon Monoxide (CO) detection systems.



62-541-Marine Surface Mount Models: 62-541-Marine-WT (White) 62-541-R-Marine-WT (White) CASE DIMENSIONS: 3.5" W x 2.5" H x 1.5" D 62-542-Marine Flush Mount Models: 62-542-Marine-WT (White) 62-542-R-Marine-WT (White) CASE DIMENSIONS: 4.5" W x 3.25" H x 1.25" D